

Material Safety Data Sheet

in accordance with EC Directive
91/155/EEC



Printed: 20.10.08

Revised: 20.10.08

Revision: 07

Page 1 of 8

XEIKON V3.3 Toner

1. Identification of the Substance and of the Company

1.1 Identification of the Substance or Preparation

Toner V3 Cyan	Product Code : 60744
Toner V3 Magenta	Product Code : 60745
Toner V3 Yellow	Product Code : 60746
Toner V3 Black	Product Code : 60747

1.2 Use of the Substance/Preparation :

Marking material for XEIKON high speed digital colour Printer

1.3 Manufacturer / Supplier Identification

PUNCHGRAPHIX INTERNATIONAL NV
Duwijkstraat 17
B-2500 Lier - Belgium
Tel. : (+32)-3-443.13.11
Fax : (+32)-3-443.13.09

PUNCHGRAPHIX AMERICAS Inc
1375 E Irving Park Rd
Itasca, IL 60143
Tel. : (1)-877-934-5667
Fax : (1)-630-438-7916

For Information call :

Phone No. : (+32)-3-443.13.11

Emergency Phone No. : (+32)-3-443.13.11

Material Safety Data Sheet
in accordance with EC Directive
91/155/EEC



XEIKON V3.3 Toner

2. Composition / Information on Ingredients

Substance or Preparation : Preparation

Ingredients Common Name CAS number	Content (%)	EINECS/ ELINCS	Symbol	R-Phrase
All toner formulations				
Polyol Resin 186359-26-2	>85	Not applicable	Not applicable	Not applicable
Organic Salt 42405-40-3	<5	- 403-360-0	F, Xn, N	R11, R22, R50/53
Colour Specific				
Organic Pigment Yellow 77804-81-0	<10	287-770-4 -	Not applicable	Not applicable
Organic Pigment Carbon Black 1333-86-4	<10	215-609-9 -	Not applicable	Not applicable
Organic Pigment 1 Magenta 68227-78-1	<5	269-389-4 -	Not applicable	Not applicable
Organic Pigment 2 Magenta 5280-68-2	<5	226-103-2 -	Not applicable	Not applicable
Organic Pigment Cyan 147-14-8	<10	205-685-1 -	Not applicable	Not applicable

The full text of each relevant R phrase are listed at heading 16.

Material Safety Data Sheet

in accordance with EC Directive
91/155/EEC



Printed: 20.10.08

Revised: 20.10.08

Revision: 07

Page 3 of 8

XEIKON V3.3 Toner**3. Hazards Identification**

This preparation is not classified as dangerous according to Directive 1999/45/EC.
This preparation is not classified as dangerous according to Directive 76/769/EEC.

Adverse Human Health Effects :

Not applicable in normal use

Carcinogenicity :**Cyan, Yellow, Magenta toner :**

This product does not contain the carcinogenic substances which are listed in NTP, IARC and are regulated by OSHA

Black toner :

Carbon Black was reclassified as a Group 2B by IARC in 1996 based on the result of only the inhalation study in rats. However there was not observed the incidence of tumours on the test results on dermal or oral studies. Also 2-years inhalation study using a typical toner containing carbon black showed no association between toner exposure and animal tumours.

Environmental Effects :

Not applicable in normal use.

Physical and Chemical Hazards :

Not applicable in normal use.

4. First Aid Measures

Immediate medical attention is not required.

Inhalation

Gargle with water, move to place in fresh air. If unsuccessful, get medical attention.

Skin Contact

Wash thoroughly with soap and water.

Eve Contact

Immediately wash eyes with plenty of water. If unsuccessful, get medical attention.

Ingestion

Dilute stomach contents with several glasses of water. If unsuccessful, get medical attention.

Material Safety Data Sheet

in accordance with EC Directive
91/155/EEC



Printed: 20.10.08

Revised: 20.10.08

Revision: 07

Page 4 of 8

XEIKON V3.3 Toner

5. Fire Fighting Measures

Extinguishing Media

CO₂, dry chemicals, foam or water.

Specific Method

Generally by sprinkling or extinguisher.

Special Protective Equipment for Fire-Fighters

Wear full bunker gear in case of burning in large quantities.

6. Accidental Release Measures

Personal Precautions

Minimize inhalation of dust

Environment Precautions

Keep product out of sewers and watercourses.

Methods for Cleaning Up

If spilled, sweep up or pick up by vacuum cleaner (rated for toner extraction). Remove residue with soap and water.

7. Handling and Storage

7.1 Handling (technical measures, precautions, safe handling material)

Do not handle in areas where wind blows

Flying powder may enter eyes.

Minimize breathing dust.

7.2 Storage (technical measures, storage conditions, packaging material)

Avoid direct sunlight.

Do not keep this over 35 degrees centigrade.

Do not put on the ship's deck.

Keep out of reach of children.

7.3 Specific Use(s)

Only for Xeikon high speed digital Colour Printers

8. Exposure Controls / Personal Protection

8.1 Exposure Limit Values :

not applicable

Material Safety Data Sheetin accordance with EC Directive
91/155/EEC

Printed: 20.10.08

Revised: 20.10.08

Revision: 07

Page 5 of 8

XEIKON V3.3 Toner**8.2 Exposure Control :****8.2.1 Occupational Exposure Control****8.2.1.1 Respiratory Protection :**
None required under normal conditions of use.**8.2.1.2 Hand Protection :**
None required under normal conditions of use.**8.2.1.3 Eye Protection :**
None required under normal conditions of use.**8.2.1.4 Skin and Body Protection**
None required under normal conditions of use.**8.2.2 Environmental Exposure Control :**

No precautions should be needed under normal use.

9. Physical and Chemical Properties**9.1 General Information**

Form : Powder

Colour: Black, Cyan, Yellow or Magenta (depending upon the toner formulation)

Odour : Slightly plastic odour

9.2 Important Health, Safety and Environmental Information

pH :	not applicable	Measuring Concentration(%) :	-
Boiling Point(°C) :	not applicable		
Flash Point(C) :	not applicable		
Flammability :	Not flammable		
Explosion Properties :	This product is considered a non explosive material under normal use condition.		
Oxidising Properties :	This product is considered a non oxidizing material under normal use condition.		
Evaporation Rate(Butyl acetate=1):	not applicable		
Vapour Pressure(Pa) :	not applicable	Measuring Temp.(°C)	
Vapour Density(AIR=1) :	not applicable		
Density (g/cm3) :	approx.1,2	Measuring Temp.(°C) :	25
Viscosity :	not applicable	Measuring Temp.(°C) :	-

Material Safety Data Sheetin accordance with EC Directive
91/155/EEC

Printed: 20.10.08

Revised: 20.10.08

Revision: 07

Page 6 of 8

XEIKON V3.3 Toner**Solubility**

Water Solubility (g/L) : Insoluble Measuring Temp.(°C) : -
Other Solvent name : not available
Other Solvent Solubility(g/L) : - Measuring Temp.(°C) : -
Octanol/Water Partition Coefficient: not available

9.3 Other Information

Melting pointy (°C) : approx. 110°C

10. Stability and Reactivity**10.1 Conditions to Avoid :**

Not applicable in normal use.

10.2 Materials to Avoid :

Not applicable in normal use.

10.3 Hazardous Decomposition Products :

not applicable

11.Toxicological Information**Acute Toxicity**

Acute Oral Toxicity (LD50) Rat : 5000 mg/kg or over

Acute Dermal Toxicity : not available

Acute Inhalation Toxicity : not available

Sensitization

Acute Skin Irritation (PII) : non-irritant

Acute Eye Irritation : not available

Acute Allergenic Effects : non-skin sensitive

Specific Effects**Carcinogenicity :**

In 1996 IARC reevaluated Carbon Black as a Group 2B carcinogen (possible human carcinogen). This evaluation is given to carbon black for which there is inadequate human evidence, but sufficient animal evidence. The latter is based upon the development of lung tumours in rats receiving chronic inhalation exposures to free carbon black at levels that induce particle overload of the lung. Studies performed in animal models other than rats have not demonstrated an association between carbon black and lung tumours. Moreover, 2-years cancer bioassay using a typical toner preparation containing carbon black did not demonstrate an association between toner exposure and tumour development in rats.

Material Safety Data Sheet

in accordance with EC Directive
91/155/EEC



Printed: 20.10.08

Revised: 20.10.08

Revision: 07

Page 7 of 8

XEIKON V3.3 Toner

For other colours : No data available

Mutagenicity :

Ames test ; not available

Effects on The Reproductive System :

No data is available on this product.

Teratogenic :

not available

12. Ecological Information

12.1 Ecotoxicity

Acute Toxicity for Fish (LD50) : over 500 mg/l (mg/l/96hr)

Acute Toxicity for Daphnia (EC50) : not available (mg/l/48hr)

Algae Inhibition Test (IC50) : not available (mg/l/72hr)

12.2 Mobility :

not available

12.3 Persistence / Degradability :

not available (deinkability = ability to recycle the printed paper : OK)

12.4 Bioaccumulation Potential :

not known in bioaccumulation

12.5 WGK classification

Classification according to the "Verwaltungsvorschrift wassergefahrende Stoffe"
WGK 2:hazard to waters.

12.6 Other Adverse Effects :

Not available

13. Disposal Consideration

Recommended Methods for Safe Environmentally Preferred Disposal:

Used toner should be disposed of in an environmentally appropriate manner and in accordance with governmental regulations. Do not incinerate,

14. Transport Information

International Regulations

Material Safety Data Sheetin accordance with EC Directive
91/155/EEC

Printed: 20.10.08

Revised: 20.10.08

Revision: 07

Page 8 of 8

XEIKON V3.3 Toner

RID/ADR : not applicable
DOT 49 CFR : not applicable
ADNR : not applicable
IMDG Code : not applicable
ICAO TI/ IATA DGR : not applicable
The UN Classification Number : not applicable

Specific Precautionary Transport Measures

Avoid direct sunlight. Do not keep this over 35 degrees centigrade. Do not put on the ship's deck.

Specific Materials to Avoid :

None in normal use.

15. Regulatory Information**Regulations**

This preparation is not classified as dangerous according to Directive 1999/45/EC.
This preparation is not classified as dangerous according to Directive 76/769/EEC.

16. Other Information**The full Text of R-Phrases Referred to under Heading 2 and 3 :**

R11:Highly flammable.

R22:Harmful if swallowed.

R50/53:Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

References:

1)IARC(1996) "IARC Monograph on the Evaluation of the Carcinogenic Risk of Chemicals to Humans, Vol.65, Printing Process and Printing Inks, Carbon Black and Some Nitro Compounds", Lyon, pp 149-'261

2)H.Muhle, B.Bellman, O.Creutzenberg, C.Dasenbrock, H.Emst, R.Kilpper, J.C.MacKenzie, P.Morrow, U.Mohr, S.Takenaka and R.Mermelstein(1991) ""Pulmonary Response to Toner upon Chronic Inhalation Exposure in Rats" Fundamental and Applied Toxicology 17,pp280-299

Note :

The data given is based on the current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the product properties.